

ADAPTEC

SLIMSCSI® | 1460

For portable PCs

Product Benefits

- Up to 6 times faster than parallel port
- Compatible with today's popular operating systems: DOS, Windows® 95, Windows NT®, Windows® 3.x and OS/2
- Multiple cable options to support all SCSI devices
- Full Plug-and Play support for Windows 95
- Connect up to 3 SCSI peripherals via daisy-chain
- EZ-SCSI® software for managing SCSI peripherals
- CardWizard Pro™ software for Windows 3.1 and DOS

For Fast, Easy Connections To All SCSI Devices

If you need the flexibility to connect your portable PC to a wide range of SCSI peripherals and operating systems, then the Adaptec SlimSCSI 1460 is a must for you. With SlimSCSI, installation is a breeze. Simply slide SlimSCSI 1460 into your PC Card slot and attach CD-ROM drives, hard disk drives, scanners, and other popular peripherals to your portable system.



Dramatically Improve Your Performance
With SlimSCSI, your peripherals will run up to 6 times faster than with a parallel port connection. Imagine copying 100MB of data in just 75 seconds, instead of eight minutes. You'll save precious time when you're on the move—and you'll save precious battery life, too.

Simple To Install

SlimSCSI is compatible with today's most popular operating systems, including DOS, Windows 3.x, Windows NT and OS/2. And SlimSCSI installs flawlessly

under Windows 95. Slide SlimSCSI into a PC Card slot, connect your SCSI device, point and click, and you're ready!

Device Support

- Iomega Zip or Jaz removable media drives
- SyQuest removable media drives
- Hard disk drives
- CD-Recordable drives
- CD-ROM drives
- Most brands of magneto-optical (MO) devices
- Scanners

Trust Adaptec—The #1 Choice for SCSI

Adaptec is the industry standard in SCSI connections, guaranteeing great performance and the utmost in reliability and compatibility. All Adaptec SCSI products are backed by a 5-year, limited warranty and full technical support for one year.

SLIMSCSI® | 1460

Adaptec, Inc.
691 South Milpitas Boulevard
Milpitas, California 95035
Tel: (408) 945-8600
Fax: (408) 262-2533

Adaptec Europe - Belgium
Tel: (32) 2-352-34-11
Fax: (32) 2-352-34-00

Adaptec Japan - Tokyo
Tel: (81) 3-5365-6700
Fax: (81) 3-5365-6950

Adaptec Singapore
Tel: (65) 278-7300
Fax: (65) 273-0163

Literature:
1-800-934-2766 (USA and Canada)
or (510) 732-3829

Pre-Sales Support:
1-800-442-7274 (USA and Canada)
or (408) 957-7274

World Wide Web:
<http://www.adaptec.com>
Internet ftp server: <ftp.adaptec.com>

Adaptec USA Bulletin Board
Service (BBS): (408) 945-7727
(up to 28,800 baud, using 8 bits,
1 stop bit, no parity)

Interactive Fax: (303) 684-3400

Copyright 1997 Adaptec, Inc. All rights reserved.
Adaptec, the Adaptec logo, the Adaptec tagline, APA,
SlimSCSI and EZ-SCSI are trademarks of Adaptec, Inc.,
which may be registered in some jurisdictions. Microsoft,
MS-DOS, Windows, Windows 95, and Windows NT are
registered trademarks of Microsoft Corporation, used
under license. Card Wizard Pro is a trademark of
SystemSoft, used under license. All other trademarks
used are owned by their respective owners.

Information supplied by Adaptec, Inc., is believed to
be accurate and reliable at the time of printing, but
Adaptec, Inc., assumes no responsibility for any errors
that may appear in this document. Adaptec, Inc.,
reserves the right, without notice, to make changes in
product design or specifications. Information is subject
to change without notice.

P/N 980298-021 10/97 Printed in U.S.A.

Technical Specifications

Operating Systems:	MS-DOS® (5.x, 6.x), Microsoft® Windows 95, Windows NT 3.51 and 4.0, Windows 3.x, Windows for Workgroups (3.1, 3.11), DR DOS, OS/2, 2.x, Warp
Data Transfer Rates:	Up to 2MB/sec PC Card bus rate (16-bit) Up to 10MB/sec synchronous burst rate on SCSI bus
Capacity:	Up to 3 daisy-chained SCSI devices
Cable Options:	50-pin low-density (SCSI-1), and a 50-pin high- density (SCSI-2) cable Free DB25-pin cable offer available in kit
Power Consumption:	.3 W typical .2 W standby mode
Size:	PC Card Type II
SCSI Data Format:	8-bit with automatic parity generation
Termination Power:	Internal active termination provided
UPC:	7 60884 12981

System Requirements

- Portable PC with PC Card Type II, Type III, or Toshiba Type IV sockets
- MS-DOS (5.x, 6.x), Microsoft Windows 95, Windows NT 3.51 and 4.0,
Windows 3.x, Windows for Workgroups (3.1, 3.11), DR DOS, OS/2, 2.x, Warp

Package Includes

- SlimSCSI 1460 PC Card-to-SCSI Adapter
- Two detachable cables, with low-density SCSI-1 and high-density SCSI-2 connectors
- Free offer for optional DB-25 cable
- SlimSCSI 1460 User's Guide
- EZ-SCSI software
- Software drivers for Windows 95, Windows NT and OS/2
- CardWizard Pro software diskettes for DOS and Windows 3.1
- Registration card